

get the **edge**...



introducing the

Titan 'EDGE'

edge-to-edge glass technology

contemporary elegance



TITAN
ALUMINIUM

edge-to-edge glazing

with ultimate performance

the **future**
starts here...

design

With unrivalled intelligent styling, thermal efficiency, security and simple installation, the 'Edge' rooflight solution ticks every box.

Its polished edge to edge glass exterior is not only a stunning evolution of its rivals, but in turn brings many practical benefits. Its clever design allows any water to simply glide off its surface, and not be hindered by perimeter sealants or protruding frames. Standing only 63mm above the roof upstand, it will blend seamlessly into any project.

Whilst allowing maximum light to flood in, the 'Edge' is constantly working very hard to keep the unwanted heat out, and the ambient room temperature constant, giving you the benefit of year-round comfort and performance.

A very welcomed standard feature of the 'Edge' is laminated security glass to the inner panel. This addition gives you the peace of mind that firstly, it is very difficult to penetrate from outside, and secondly, in the event that the inner pane is compromised, laminated glass is shatterproof so will provide optimum safety.

Installation couldn't be easier. The 'Edge' rooflight is delivered in one piece, its fixing straps already attached. It has no trims or 'extra bits' to put on afterwards, so has nothing to get lost or damaged.



in a class of its own...

Titan 'EDGE'
contemporary elegance

safety first

With security and safety being paramount.

The 'Edge' flat rooflight is fastened from inside, it has no external fixings that could be removed. With 6mm toughened safety glass outside, and 6.4mm laminated safety glass inside, as standard, 'The Edge' provides the ultimate combination of security and peace of mind.

performance

Comprising the ultimate in thermal insulation.

The 'Edge' has a very careful selection of high performance glazing components. It benefits from both low maintenance solar reflective glass outside and low emission laminated glass inside, structurally bonded into the unique super slim 'Edge' thermally broken aluminium frame, providing all year-round comfort with a typical u' value of 1.3 w/m2k (overall roof)

technical

Thermally broken aluminium frame
Structurally bonded high performance glass
Typical U value 1.3 w/m2k
Laminated safety glass to internal pane
Built in plasterboard pocket
Available in Grey (RAL 7106M) & Black (RAL 9005M)
5 degree pitch recommended

